

FCK Control cabinet - Floor cabinet

FCK 218 70 60 H

Developed in collaboration with the hydropower industry. Removable end caps and reinforced doors.



Field of application

These cabinets are designed for 19" mounting of control and relay equipment. The cabinets are designed in collaboration with the electric power industry.

Product description

The cabinets are made for mounting 19" panels on 3 levels. End caps are removable to facilitate installation.

The standard fittings include:

Ventilated plinth, roof plate with space for a title plate.

LED lighting with wall socket and automatic on/off.

19" rail with level markings in the backplane.

Double 19" planes with level markings in the door. Earth rail with approx. 130 overlaps.

The cabinet is equipped with a door stop.

Cable fastening hinge lock side

1 Din rail hinge side

Mounting area 19": Number of height units - 40 HU in the door and 43 HU in the rear.

Max construction depth:

370 mm / W=700 mm

520 mm/ W=800 mm

NB! Order number = outer dimensions of the enclosure - in cm

In the order number:

H= right hung

V= left hung

HS= right hung plain door, not 19"

VS= left hung plain door, not 19"

Surface treatment

Powder coating with textured surface, RAL 7035 (light grey). Special colours on request.

Specifications

- Developed in collaboration with the electric power industry
- Removable end caps
- Reinforced doors

More information

- Article number: 413007
- Order number: FCK 218 70 60 H
- Dimensions height x width x depth (mm): 2180 x 700 x 600
- Execution: Right-handed door
- Weight (kg): 114
- Connection openings lower piece : Rectangular openings

Construction

The frame structure of the cabinets consists of a specially shaped profile that allows for unlimited installation possibilities. The doors of the cabinets are reinforced to be loaded with heavy mounting accessories.