

DCU IP55 - Technical / Outdoor cabinet

436001

Outdoor cabinet for demanding environments, made of hot-dip galvanised sheet metal with 10 mm insulation. Three-point spanionet locking and prepared for Assa cylinders.



Field of application

Our DCU cabinets are designed to be used outdoors as technology cabinets for broadband, telecom, traffic monitoring and similar applications. Our tipping rack cabinet (DCU 80 60 20) is ideal for smaller broadband installations.

Product description

Our outdoor cabinets are made of hot-dip galvanized sheet steel and lacquered. Therefore, our cabinets are able to protect equipment in demanding environments.

The DCU cabinets are equipped with a 10mm insulation mat. The cabinets can also be manufactured in EMC or UL design if desired.

If meter cabinets are to be installed, check with the network owner whether you should use extra foundations (FU) to obtain the correct placement of meter cabinets vertically.

Specification

Lock housing for ASSA cylinder
Detachable flanges for easy fiber and cable assembly
Fitted door stoppers*
Pitched roof*
Roof with drip edge*
1x25/2x25 HE 19" **mounting***
3HE in the Tipping Rack Cabinet
***Not in tipping rack cabinet (DCU 80 60 20)**

Construction:

The cabinets have fixed back panels and end panels. The double-collared daytime opening and the closed front pillars provide the highest level of stability and tightness. The hinges are concealed and recessed, as well as screwed into the cabinet frame. The doors can be easily lifted off with an opening angle of 175°. The locks are of the 3-point espagnolette type with a lock housing for the ASSA cylinder as standard and are protected with a protective cover. Ground connection bolts are available in doors as well as in cabinet stands. The cabinets

Specifications

- Doors with concealed hinges
- Insulating mat 10mm
- Easy to install

More information

- Article number: 436001
- Order number: DCU 120 68 60 Green
- E-number: 2529140
- Dimensions height x width x depth (mm): 1200 x 680 x 600
- Execution: Single door
- Weight (kg): 120



are easily mounted on foundations, additional foundations or plinths.

[Surface treatment](#)

RAL 7035 grey or RAL 6009 green

[Produktlänk](#)

http://www.elkapsling.se/en/product/technology-outdoor-cabinet-dcu-ip55/?attribute_pa_bestallningsnummer=dcu-120-68-60-green